

FEEL BETTER.  
TRAVEL FARTHER.

# SHOCKWAVE

## MARINE SUSPENSION SEATING

### HOW TO CLEAN YOUR S5 SENTINEL SUSPENSION MODULE

- 1 Using a soft cloth, wipe all surfaces of the S5 or Sentinel Suspension Module with fresh water. Open deck boats can hose off the suspension modules if needed.
- 2 Allow to dry
- 3 Spray LPSI, Boeshield (or equivalent) corrosion inhibitor on terry or microfiber cloth and wipe all metallic and painted surfaces and hardware.
- 4 Ensure all areas surrounding bolt heads and nuts are thoroughly cleaned and lubricated to decrease chance of corrosion
- 5 Gently wipe shock shaft with a thin layer of LPSI, Boeshield (or equivalent) corrosion inhibitor. Clean off excess to avoid particulate from sticking to the shock shaft during operations.
- 6 All accessories (slide, swivel slide) can have LPSI, Boeshield or equivalent applied.
- 7 Application of LPSI or Boeshield should occur after every trip or once every 30 days.
- 8 Wipe Corbin2 or Commander Seats with Marine grade upholstery cleaner.
- 9 **\*Optional.\*** All bolt heads and nuts can be coated with LPS3 if desired for added corrosion resistance.

