FEEL **BETTER.** Travel **farther.**

SHOCKWAVE MARINE SUSPENSION SEATING

Shockwave S5-SS Suspension Base

SW-09108

The NEW Shockwave S5-SS stainless steel suspension base is a premium product built to last a lifetime. It is best suited for professional mariners boating in saltwater environments prone to high salinity and humidity. It offers a smoother, safer and more comfortable ride, providing boaters an experience they have never experienced before.

This S5-SS suspension is electropolished and welded using 316 stainless steel, and it provides the same forward action suspension design that boaters have come to expect in our recreational products. This suspension base protects occupants from the shock of wave impact in heavy seas, allowing recreational boaters to stay out longer and travel farther with less fatigue. It's the perfect solution for offshore fishing in rough water.



NEW

Easy to install and can be paired with almost any seat

4" [I00mm] travel custom tuned and valved air spring shock

Designed and built in Canada

Spring and Shock	FOX Rhythm, Air Spring and Shock with Adjustable Rebound and Compression	Cabin Use	Yes
Construction	Electropolished Welded 316 Stainless Steel	Outside Deck Use	Best for Saltwater with High Salinity and Humidity
Suspension Design	4-Link Forward Action	Size	H: 9.0in [229mm] W: 10.8in [274mm]
Overall Performance	Best for Professional Mariner's Use in Heavy Seas	Weight	L: 16.3in [414mm] 30.0 lbs [13.6 kg]
Warranty	5 Year – Limited Warranty	Weight Capacity	Up to 300 lbs [136.1 kg]

S5 Product Line Accessories

SHOCKWAVE MARINE SUSPENSION SEATING

Shockwave Shock Pump

SW-01983-PKG

A shock pump is required to properly operate all Shockwave S5 suspension bases. The high-pressure Shockwave shock pump features a pressure gauge and bleed valve for simple adjustment.

- The S5 suspension base must be pressurized at install or it will not operate properly
- Factory pressure setting is approximately IOO-I50 psi
- The shock should be pressurized to match the weight (in pounds) of the occupant
- Subset as needed, after install, to adjust shock pressure (psi) for a heavier or lighter person
- Maximum inflation pressure of 350 psi



